



CE

Power	100 W	Voltage	230 V
Luminous flux*	8400 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	100 °
IK	07	Protection class	IP65



See more on dedicated page [➔](#)




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI029051NW_TRIPOD_PW
Power	100 W
Nominal current	405 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	8400 lm (120°)
Luminous flux**	8300 lm (360°)
Light efficiency	84 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP65
Colour	Black
Dimension (axbxc)	2x(205x170x30) + 2000 wire mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC
Other	Info to instrukcji: zaw. 2 źródła św. o EEI F, ,



*Applies to the LED source used. **Luminaire luminous flux