


120  
lm/W



CE

Power	<b>14 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1680 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>120 °</b>
Protection class	<b>IP20</b>		



 User manual



 Declaration of Conformity

Technical data:

Product code	SLI028209_PW
Power	14 W
Nominal current	115 mA
Voltage	230 V
Energy consumption	14 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	1680 lm (360°)
Luminous flux**	1400 lm (360°)
Light efficiency	120 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	120 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 +40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
Protection class	IP20
Colour	White
Dimension (axbxc)	1192x25x36 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC
Other	Maks 7 sztuk w lini/Max 7 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux