







## spring clamp terminal block 1 level earth connection 16 mm<sup>2</sup>

Series	HTE
Code	HT340
Type	HTE.16
HS code	85369010
Colour	Yellow-green
<b>TECHNICAL FEATURES</b>	
Function/Type	Earth terminal blocks
Rated cross-section	16 mm <sup>2</sup>
<b>Connecting capacity</b>	
Flexible wire	1.5-25 mm <sup>2</sup>
Rigid wire	1.5-25 mm <sup>2</sup>
Wire with ferrule - ferrule type	16 mm <sup>2</sup> – WP160/22
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum current (rated cross-section)	–
Caliber	A7
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	–
Section (min-max)	18-4 (AWG)
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
Maximum voltage AC/DC	630 V
Operating temperature Min/Max	-40 °C / +80 °C
Insulation stripping length	18 mm
Width (pitch)	12 mm
Length	80 mm
Height mounted on TH35-7.5/TH35-15/G32	56 / 64 / – mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
Grey	HMT.16/PT (cod. HM341GR)
Blue	–
Thickness	1.5 mm
<b>Cross-connection</b>	
Cross-connection identification strip	–
Coloured partition plate	DFH/4/R (cod. DH04R)
Cross-connection barrier	–
Test plug	SDD/1 (cod. DD001)
Modular test plug	–
End section for modular test plug	–
<b>Marking</b>	
Single marking tag	CNU/8/51 (cod. NU0851S)
Single marking tag for pitch insertion	–
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BT0 (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
<b>APPROVALS AND MARKINGS</b>	
    	



1 For more details on accessories, refer to the relevant chapters

## DESCRIZIONE DEL PRODOTTO

spring clamp terminal block 1 level earth connection 16 mm<sup>2</sup>