



screw terminal block fuse-holder with alarm signal, 4 mm<sup>2</sup>, beige

Series	SFR – CBF – FPL
Code	SF948
Type	SFR.4/C48
HS code	85369010
Colour	Beige
<b>TECHNICAL FEATURES</b>	
Function/Type	Fuse-holder 5x20 with alarm
Rated cross-section	4 mm <sup>2</sup>
<b>Connecting capacity</b>	
Flexible wire	0.2-6 mm <sup>2</sup>
Rigid wire	0.2-6 mm <sup>2</sup>
Wire with ferrule - ferrule type	4 mm <sup>2</sup> – WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	6.3 A
Caliber	A4
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	6.3 A
Section (min-max)	20-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	11 mm
Tightening torque value (nom. / max.)	0.5 / 1.2 Nm
Width (pitch)	8 mm
Length	52 mm
Height mounted on TH35-7.5/TH35-15/G32	52 / 60 / 56 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
Grey	SFR/PT/GR (cod. SF701GR)
Blue	–
Beige	SFR/PT (cod. SF701)
Thickness	1.5 mm
<b>Cross-connection</b>	
Model A)	–
Model B)	–
Rated current carrying capacity IEC/ATEX	–
Cross-connection identification strip	–
Coloured partition plate	DFU/3/R (cod. DU03R)
Cross-connection barrier	–
Test plug socket	–
Test plug	–
<b>Marking</b>	
Snap-on numbering strip	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag	–
Fuse type	5x20 mm (1)
Conductive element	CO/5 (cod. VL103)
Light alarm circuit (12...48 V)	Already mounted
Light alarm circuit (110...230 V)	–
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
<b>Mounting rail</b>	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	–
<b>APPROVALS AND MARKINGS</b>	
	



\* Suitable for 5x20 mm fuses\* Alarm LED circuit already mounted (12-48 V)\* Fuse available separately  
1 For more details on accessories, refer to the relevant chapters

## DESCRIZIONE DEL PRODOTTO

screw terminal block fuse-holder with alarm signal, 4 mm<sup>2</sup>, beige