



COMPOSIZIONE ANIMALE		
Struttura (dopo)	Modificazioni di qualità (R) e di TPLA	Longevità (età in anni)
4	0-0-0-0-0-0-0-0-0-0	50
6	0-0-0-0-0-0-0-0-0-0	75
8	0-0-0-0-0-0-0-0-0-0	100
10	0-0-0-0-0-0-0-0-0-0	125
12	0-0-0-0-0-0-0-0-0-0	150
14	0-0-0-0-0-0-0-0-0-0	175
16	0-0-0-0-0-0-0-0-0-0	200
18	0-0-0-0-0-0-0-0-0-0	225
20	0-0-0-0-0-0-0-0-0-0	250

Modular multi-pole terminal, 4 mm², beige

Series	BPL-TPL
Code	BP310
Type	BPL4/PS/A
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through with solder terminal
Rated cross-section	4 mm²
Rated cross-section	–
Connecting capacity	
Flexible wire	0.5-4 mm²
Rigid wire	0.5-6 mm²
Wire with ferrule - ferrule type	4 mm² – WP40/16
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	32 A
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	20 A
Section (min-max)	18-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	9 mm
Tightening torque value (nom. / max.)	0.5 / 0.7 Nm
Dimension	20x24x36 mm (AxBxH)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	–
Insulated bushing	–
APPROVALS AND MARKINGS	
	



DESCRIZIONE DEL PRODOTTO

Modular multi-pole terminal, 4 mm², beige