

CE

Power	<b>12 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>2700/3300/4000 K</b>	Light colour	<b>CCT</b>
Beam angle	<b>35 °</b>	UGR	<b>&lt;19</b>
Protection class	<b>IP20</b>		




 User manual



 Declaration of Conformity

Technical data:

Product code	WLD+40040_CCT
Power	12 W
Nominal current	230 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1200 lm (360°)
Luminous flux**	750 lm (360°)
Light efficiency	100 lm/W
Luminous intensity	2580 cd
Colour temperature	2700/3300/4000 K
Light colour	CCT
Beam angle	35 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Protection class	IP20
Colour	White
Dimension (axbxc)	204x23x42 mm
For use	Inside
Assembly method	NA SZYBĘ
Application	Inside
Made in	PRC
Other	CCT ,



\*Applies to the LED source used. \*\*Luminaire luminous flux