



CE

| | | | |
|--------------------|-------------------------|--------------|---------------|
| Power | 12 W | Voltage | 48 V |
| Colour temperature | 2700/3300/4000 K | Light colour | CCT |
| Beam angle | 35 ° | UGR | <19 |
| Protection class | IP20 | | |



 User manual

Technical data:

| | |
|------------------------------|------------------|
| Product code | WLD+40011_CCT |
| Power | 12 W |
| Nominal current | 230 mA |
| Voltage | 48 V |
| Energy consumption | 12 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 1200 lm (360°) |
| Luminous flux** | 750 lm (360°) |
| Light efficiency | 100 lm/W |
| Luminous intensity | 2580 cd |
| Colour temperature | 2700/3300/4000 K |
| Light colour | CCT |
| Beam angle | 35 ° |
| UGR | <19 |
| RA | >90 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 50000 h |
| Housing material | AL+PC |
| Protection class | IP20 |
| Colour | Czarny |
| Dimension (axbxc) | 204x23x42 mm |
| For use | Inside |
| Assembly method | NA SZYŃĘ |
| Application | Inside |
| Made in | PRC |
| Other | CCT , |



*Applies to the LED source used. **Luminaire luminous flux