



CE


| | | | |
|------------------|-----------------------|--------------------|-------------------------|
| Power | 40 W | Voltage | 230 V |
| Luminous flux* | 5000 lm (360°) | Colour temperature | 2700/4000/6000 K |
| Light colour | CCT | Beam angle | 115 ° |
| Protection class | IP20 | | |



 User manual

Technical data:

| | |
|------------------------------|---|
| Product code | SLI047301CCT_PW |
| Power | 40 W |
| Nominal current | 175 mA |
| Voltage | 230 V |
| Energy consumption | 40 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | Yes |
| Power factor | 0.95 |
| Useful luminous flux* | 5000 lm (360°) |
| Luminous flux** | 4000 lm (360°) |
| Light efficiency | 125 lm/W |
| Colour temperature | 2700/4000/6000 K |
| Light colour | CCT |
| Beam angle | 115 ° |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | Black |
| Dimension (axbxc) | 1203x42x37 mm |
| For use | Inside |
| Assembly method | natynkowy, zwieszany |
| Application | Inside |
| Made in | PRC |
| Other | Funkcja zmiany barwy światła 2700K/4000K/6000K , |



*Applies to the LED source used. **Luminaire luminous flux