


**CE**

---

Power	<b>50 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6250 lm (360°)</b>	Colour temperature	<b>2700/4000/6000 K</b>
Light colour	<b>CCT</b>	Beam angle	<b>115 °</b>
Protection class	<b>IP20</b>		

---

 User manual

Technical data:

Product code	SLI047302CCT_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	6250 lm (360°)
Luminous flux**	5000 lm (360°)
Light efficiency	125 lm/W
Colour temperature	2700/4000/6000 K
Light colour	CCT
Beam angle	115 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	1503x42x37 mm
For use	Inside
Assembly method	natynkowy, zwieszany
Application	Inside
Made in	PRC
Other	Funkcja zmiany barwy światła 2700K/4000K/6000K ,



\*Applies to the LED source used. \*\*Luminaire luminous flux