



CE

Power	<b>25/40/45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6500 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Light colour	<b>CCT</b>	Beam angle	<b>90°</b>
Protection class	<b>IP20</b>		



 Declaration of Conformity

Technical data:

Product code	SLI035075CCT_PW
Power	25/40/45 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6500 lm (360°)
Luminous flux**	3000/4800/5400 lm (360°)
Light efficiency	144 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	90 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Protection class	IP20
Colour	White
Dimension (axbxc)	620x620x34 mm
For use	Inside
Assembly method	natynkowy, podtynkowy
Application	INT
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



\*Applies to the LED source used. \*\*Luminaire luminous flux