



Power **12 W**

Voltage **48 V**


Colour temperature **2700 K**

Light colour **WW**

Beam angle **24 °**

Protection class **IP20**



 User manual

**Technical data:**

|                              |                |
|------------------------------|----------------|
| Product code                 | WLD+70023WW    |
| Power                        | 12 W           |
| Nominal current              | 210 mA         |
| Voltage                      | 48 V           |
| Energy consumption           | 12 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power factor                 | 1              |
| Useful luminous flux*        | 1260 lm (360°) |
| Luminous flux**              | 625 lm (360°)  |
| Light efficiency             | 105 lm/W       |
| Luminous intensity           | 4000 cd        |
| Colour temperature           | 2700 K         |
| Light colour                 | WW             |
| Beam angle                   | 24 °           |
| RA                           | 80             |
| Light source included        | Yes            |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20 to +40 °   |
| Lifespan                     | 17000 h        |
| Housing material             | AL+PC          |
| Protection class             | IP20           |
| Colour                       | Czarny         |
| Dimension (axbxc)            | 50x110x170 mm  |
| For use                      | Inside         |
| Assembly method              | NA SZYBĘ       |
| Application                  | Inside         |
| Made in                      | PRC            |



\*Applies to the LED source used. \*\*Luminaire luminous flux