

102
lm/W



CE

Power **10 W**

Voltage **48 V**


Colour temperature **2700 K**

Light colour **WW**

Beam angle **120 °**


Protection class **IP20**



 User manual

Technical data:

| | |
|------------------------------|----------------|
| Product code | WLD+70020WW |
| Power | 10 W |
| Nominal current | 200 mA |
| Voltage | 48 V |
| Energy consumption | 10 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 1020 lm (360°) |
| Luminous flux** | 625 lm (360°) |
| Light efficiency | 102 lm/W |
| Colour temperature | 2700 K |
| Light colour | WW |
| Beam angle | 120 ° |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | AL+PC |
| Protection class | IP20 |
| Colour | Czarny |
| Dimension (axbxc) | 90x150 mm |
| For use | Inside |
| Assembly method | NA SZYŃĘ |
| Application | Inside |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux