





| | | | |
|--------------------|---------------|--------------|---------------|
| Power | 18 W | Voltage | 48 V |
| Colour temperature | 2700 K | Light colour | WW |
| Beam angle | 24 ° | UGR | <19 |
| Protection class | IP20 | | |



 User manual

Technical data:

| | |
|------------------------------|----------------|
| Product code | WLD+70030WW |
| Power | 18 W |
| Nominal current | 270 mA |
| Voltage | 48 V |
| Energy consumption | 18 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 1980 lm (360°) |
| Luminous flux** | 1280 lm (360°) |
| Light efficiency | 110 lm/W |
| Luminous intensity | 5700 cd |
| Colour temperature | 2700 K |
| Light colour | WW |
| Beam angle | 24 ° |
| UGR | <19 |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | AL+PC |
| Protection class | IP20 |
| Colour | Czarny |
| Dimension (axbxc) | 330x23x42 mm |
| For use | Inside |
| Assembly method | NA SZYŃE |
| Application | Inside |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux