

## PHE 15 16.7 4T TA (766 616)

- For use in wet weather conditions
- For overhead contact lines of electrical railways
- With self-testing element
- Visual indication
- Easy transport due to detachable insulating sticks
- Consisting of four elements
- Storage bag included in delivery



Ilustracje nie są wiążące

Ilustracje nie są wiążące

### Kit includes:

| Pos. No. | Part No. | Pos. No. | Part No. |
|----------|----------|----------|----------|
| 1        | 766 619  | 7        | 766 076  |
| 2        | 766 678  | 8        | 766 077  |
| 3        | 766 677  | 9        | 766 889  |
| 4        | 766 072  | 10       | 766 602  |
| 5        | 766 075  | 11       | 766 704  |
| 6        | 766 073  |          |          |

For more detailed information on these products, see Accessory chapter

| Typ<br>Nr kat.                                  | PHE 15 16.7 4T TA<br>766 616                |
|---|---|
| Nominal voltage (U <sub>N</sub> )               | 15 kV                                       |
| Type of voltage                                 | a.c.  |
| Frequency                                       | 16.7 Hz                                     |
| Total length (l <sub>Σ</sub> )                  | 4890 mm                                     |
| Insulating clearance (l <sub>i</sub> )          | 685 mm                                      |
| Insertion depth (l <sub>o</sub> )               | 1675 mm                                     |
| Length of the prod                              | 1900 mm                                     |
| Length of the operating stick (with hand guard) | 640 mm                                      |
| Length of the operating stick (end fitting)     | 2530 mm                                     |
| DB drawing No.                                  | 3 Ebgw 02.51                                |
| DB material No.                                 | 237 129                                     |
| Standard  | DIN VDE 0681-6                              |
| Design  | Complete                                    |
| For use at                                      | ☀   |
| For   | Outdoor installations                       |
| Application                                     | Overhead contact lines of electric railways |
| Version   | Single-pole                                 |
| Indication                                      | Visual                                      |
| Self-testing element                            | Yes   |
| Battery   | Lithium                                     |
| Material (test electrode)                       | St/gal Zn                                   |
| Material (test prod)                            | Glass-fibre reinforced polyester tube       |
| Material (indicator)                            | Plastic, fully insulated                    |
| Material (insulating stick)                     | Glass-fibre reinforced polyester tube       |
| Waga  | 5,09 kg                                     |
| Numer taryfy celnej (Nomenklatura scalona EU)   | 90303370                                    |
| GTIN (EAN)                                      | 4013364126091                               |
| Jed. Op.  | 1 szt.                                      |

W związku z ciągłym rozwojem technicznym zastrzegamy sobie prawo wprowadzenia zmian parametrów technicznych, konfiguracji i technologii, wymiarów, wagi i materiałów. Przedstawione ilustracje nie są wiążące.