


SZ HH 1500 (765 042)

- 20° angled operating head for HH fuses that are not easily accessible



Typ	SZ HH 1500
Nr kat.	765 042
Nominal voltage (U _N)	1 ... 36 kV
Clamping range	30 ... 50 ¹⁾ / 50 ... 90 mm
Total length (l _G)	1500 mm
Insulating clearance (l _i)	525 mm
Length (handle) (l _H)	790 mm
Insertion depth (l _o)	185 mm
Standard	DIN VDE V 0681-3
For use at	☀
For	Indoor and outdoor installations
Design	Straight clamp body
Material (insulating stick)	Glass-fibre reinforced polyester tube
Material (operating head)	Glass-fibre reinforced polyamide
Material (reducing insert)	Polyamide
Material (adjustable handle)	Polyamide
Diameter	43 mm
Colour	Grey ●
Anti-rotation plug-in coupling including end fitting	No
Type of device	Fuse tong
Waga	2,59 kg
Numer taryfy celnej (Nomenklatura scalona EU)	82055980
GTIN (EAN)	4013364093775
Jed. Op.	1 szt.

¹⁾ Only if used with reducing insert

W związku z ciągłym rozwojem technicznym zastrzegamy sobie prawo wprowadzenia zmian parametrów technicznych, konfiguracji i technologii, wymiarów, wagi i materiałów. Przedstawione ilustracje nie są wiążące.