

PHE3S60 110S CSN7774 (769 712)

■ Transport case included



Typ	PHE3S60 110S CSN7774
Nr kat.	769 712
Nominal voltage (U _N)	60 ... 110 kV
Type of voltage	a.c.
Frequency	50 Hz
Category	S
Total length (l _{G max} / l _{G min})	4470 / 2840 mm
Insertion depth (l _o)	880 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	-25 °C ... +55 °C, climatic category N
Design	complete
For use at	
For	indoor and outdoor installations
Application	switchgear installations and overhead lines
Design	single-pole
Indication	acoustic and visual
Self-testing element	yes
Material (test electrode)	copper alloy/gal Sn
Material (test prod)	glass-fibre reinforced epoxy resin tube
Material (indicator)	plastic, fully insulated
Material (insulating stick)	glass-fibre reinforced polyester tube
Waga	5,23 kg
Numer taryfy celnej (Nomenklatura scalona EU)	90303370
GTIN (EAN)	4013364242517
Jed. Op.	1 szt.

W związku z ciągłym rozwojem technicznym zastrzegamy sobie prawo wprowadzenia zmian parametrów technicznych, konfiguracji i technologii, wymiarów, wagi i materiałów. Przedstawione ilustracje nie są wiążące.