

# WLD+70051NW

WLD+70051NW

---



---

Power	<b>6 W</b>
Colour temperature	<b>4000 K</b>
Beam angle	<b>24 °</b>
Degree of protection (IP)	<b>IP20</b>

Voltage	<b>48 V</b>
Colour of light	<b>Neutral white</b>
UGR	<b>&lt;19</b>

---

## Technical data

---

Code	WLD+70051NW
Power	6 W
Nominal current	100 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	600 lm (360°)
Luminous flux**	400 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	1700 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	24 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	110x23x110 mm
For use	Inside
Assembly method	NA SZYŃĘ
Application	Inside
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity