

# SLI044029NW\_PW

SLI044029NW\_PW



Power	<b>100/150/200 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>31000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>90 °</b>
IK	<b>9</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

---

Code	SLI044029NW_PW
Power	100/150/200 W
Nominal current	900 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.97
Useful luminous flux*	31000 lm (360°)
Luminous flux**	15000-30000 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	13500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	0-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	9
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	280x145 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity

