

# WOJ+13785\_CW

WOJ+13785\_CW

---



---

|                 |                      |                    |               |
|-----------------|----------------------|--------------------|---------------|
| Power           | <b>1,2 W</b>         | Voltage            | <b>12 V</b>   |
| Luminous flux** | <b>120 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Colour of light | <b>CW</b>            | Beam angle         | <b>120 °</b>  |
| Socket          | <b>G4</b>            |                    |               |

---

## Technical data


---

|                              |               |
|------------------------------|---------------|
| Code                         | W0J+13785_CW  |
| Power                        | 1,2 W         |
| Nominal current              | 110 mA        |
| Voltage                      | 12 V          |
| Energy efficiency class      | F             |
| Energy consumption           | 2 kWh/1000h   |
| Frequency                    | 0-50HZ Hz     |
| Useful luminous flux*        | 120 lm (360°) |
| Luminous flux**              | 120 lm (360°) |
| Lamp efficacy                | 100 lm/W      |
| Colour temperature           | 6000 K        |
| Colour of light              | CW            |
| Beam angle                   | 120 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Socket                       | G4            |
| Dimension (AxBxC)            | 20x30x8 mm    |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |

## Related documents

---



 Declaration of Conformity