

# SLI035079NW\_PW

SLI035079NW\_PW

---



---

|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>40 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>4800 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Colour of light           | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP20</b>           |                    |               |

---

## Technical data


---

|                              |                 |
|------------------------------|-----------------|
| Code                         | SLI035079NW_PW  |
| Power                        | 40 W            |
| Nominal current              | 175 mA          |
| Voltage                      | 230 V           |
| Energy consumption           | 40 kWh/1000h    |
| Frequency                    | 50HZ Hz         |
| Protection class             | I               |
| Power supply included        | +               |
| Power factor                 | 0.9             |
| Useful luminous flux*        | 4800 lm (360°)  |
| Luminous flux**              | 4400 lm (360°)  |
| Lamp efficacy                | 120 lm/W        |
| Colour temperature           | 4000 K          |
| Colour of light              | Neutral white   |
| Beam angle                   | 120 °           |
| RA                           | >80             |
| Uniformity of color SDCM max | 5               |
| Dimmable                     | No              |
| Working temperature range    | -20/+40 °       |
| Lifespan                     | 26000 h         |
| Housing material             | Plastic/STAL/PP |
| Degree of protection (IP)    | IP20            |
| Colour                       | White           |
| Dimension (AxBxC)            | 595x595x33 mm   |
| For use                      | Inside          |
| Assembly method              | On the ceiling  |
| Application                  | INT             |
| Made in                      | PRC             |


## Related documents

---



 User manual



 Declaration of Conformity