

# WLD+40009\_CCT\_2F

WLD+40009\_CCT\_2F



Power	<b>17 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>2700/3300/4000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>100 °</b>	Degree of protection (IP)	<b>IP20</b>


## Technical data

Code	WLD+40009_CCT_2F
Power	17 W
Nominal current	350 mA
Voltage	48 V
Energy consumption	17 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1800 lm (360°)
Luminous flux**	750 lm (360°)
Lamp efficacy	106 lm/W
Colour temperature	2700/3300/4000 K
Colour of light	CCT
Beam angle	100 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	602x23x42 mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC
Other	CCT ,



## Related documents



 Declaration of Conformity

