

NOCTIS LUX 2

SLI029040NW_CZUJNIK



See
more

Floodlight NOCTIS LUX 2, with a power of 50 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP44




Power	50 W	Voltage	230 V
Luminous flux*	4000 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
Degree of protection (IP)	IP44		

Technical data

Code	SLI029040NW_CZUJNIK
Power	50 W
Nominal current	240 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4000 lm (120°)
Luminous flux**	3850/4000 lm (360°)
Lamp efficacy	77 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	212x206x35 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file