

SLI035082CCT_PW

SLI035082CCT_PW



Power	26/36/46 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	90 °
UGR	<19	Degree of protection (IP)	IP20

Technical data

Code	SLI035082CCT_PW
Power	26/36/46 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	46 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.95
Useful luminous flux*	6300 lm (360°)
Luminous flux**	3120/4320/5520 lm (360°)
Lamp efficacy	137 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	90 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x34 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Related documents



 User manual



 Declaration of Conformity