

# SYSTEM SHIFT BASIC GLOBE PENDANT

WLD+70037WW



See  
more

On track luminaire SYSTEM SHIFT BASIC GLOBE PENDANT, with a power of 10 W, high light efficacy 102 lm/W. Designed to be mounted on a track.



---

|                    |               |                           |             |
|--------------------|---------------|---------------------------|-------------|
| Power              | <b>10 W</b>   | Voltage                   | <b>48 V</b> |
| Colour temperature | <b>2700 K</b> | Colour of light           | <b>WW</b>   |
| Beam angle         | <b>120 °</b>  | Degree of protection (IP) | <b>IP20</b> |

---

## Technical data


---

|                              |                     |
|------------------------------|---------------------|
| Code                         | WLD+70037WW         |
| Power                        | 10 W                |
| Nominal current              | 200 mA              |
| Voltage                      | 48 V                |
| Energy consumption           | 10 kWh/1000h        |
| Frequency                    | DC Hz               |
| Protection class             | III                 |
| Power factor                 | 1                   |
| Useful luminous flux*        | 1020 lm (360°)      |
| Luminous flux**              | 625 lm (360°)       |
| Lamp efficacy                | 102 lm/W            |
| Colour temperature           | 2700 K              |
| Colour of light              | WW                  |
| Beam angle                   | 120 °               |
| RA                           | 80                  |
| Light source included        | Yes                 |
| Uniformity of color SDCM max | 5                   |
| Dimmable                     | No                  |
| Working temperature range    | -20 to +40 °        |
| Lifespan                     | 17000 h             |
| Housing material             | AL+PC               |
| Degree of protection (IP)    | IP20                |
| Colour                       | White               |
| Dimension (AxBxC)            | 90 (1200mm wire) mm |
| For use                      | Inside              |
| Assembly method              | NA SZYŃĘ            |
| Application                  | Inside              |
| Made in                      | PRC                 |

## Related documents

---



 User manual



 Declaration of Conformity