

# SLI028051NW\_PW

SLI028051NW\_PW



|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>45 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>6000 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Colour of light           | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP65</b>           |                    |               |

## Technical data


---

|                              |                           |
|------------------------------|---------------------------|
| Code                         | SLI028051NW_PW            |
| Power                        | 45 W                      |
| Nominal current              | 205 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 45 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | II                        |
| Power factor                 | 0.9                       |
| Useful luminous flux*        | 6000 lm (360°)            |
| Luminous flux**              | 5400 lm (360°)            |
| Lamp efficacy                | 133 lm/W                  |
| Colour temperature           | 4000 K                    |
| Colour of light              | Neutral white             |
| Beam angle                   | 120 °                     |
| RA                           | 80                        |
| Light source included        | Yes                       |
| Uniformity of color SDCM max | 5                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 26000 h                   |
| Housing material             | PC                        |
| Degree of protection (IP)    | IP65                      |
| Colour                       | White                     |
| Dimension (AxBxC)            | 1500x59x34 mm             |
| For use                      | Inside/Outside            |
| Assembly method              | On the ceiling, Suspended |
| Application                  | Inside/Outside            |
| Made in                      | PRC                       |
| Other                        | 2m cable with plug ,      |


## Related documents

---



 User manual



 Declaration of Conformity