



Data Sheet

Complete OBUK surface-mount enclosures

Description and Technical Characteristics of the Product:

Surface-mount enclosures are designed for mounting electrical and ICT equipment in 45x45 standard. The sockets in 60mm standard can only be mounted in a 2-module enclosure (OBUK-2/M), after replacing the screws with flat head screws, but please ensure that the frame is adjusted in relation to the fixture and the enclosure.

The components included: surface-mount enclosure (OBU), mounting bracket (SUP), masking frame (RAM).

Installation method:

Cut a hole at the desired location, in the side wall of the enclosure using the guides. If necessary, install a connector (E K/PU) connecting the enclosure to the duct. Then screw on the mounting bracket (SUP), snap in the network or computer socket and snap in the RAM masking frame.

Markings:

2-module surface-mount enclosure (metal bracket), Code: OBUK-2/M

4-module surface-mount enclosure (metal bracket), Code: OBUK-4/M

6-module surface-mount enclosure (metal bracket), Code: OBUK-6/M

Technical parameters:

Mechanical:

colours: white

dimensions (W x H x D): 84x84x40mm (OBUK-2); 82x150x40mm (OBUK-4); 82x195x40mm (OBUK-6);

material: ABS (enclosure and masking frame), metal brackets



We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.