

# Test Verification of Conformity

Verification Number: 230501326SHA-V1

On the basis of the referenced test report(s), sample(s) tested of the below product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it <them>.

Once compliance with all product relevant **CE** mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Applicant Name & Address:	Shanghai JA Solar Technology Co., Ltd. No. 118, Lane 3111, West Huancheng Road, Fengxian District, Shanghai, 201401, China
Product Description:	Mono Crystalline Silicon Photovoltaic (PV) Modules
Ratings & Principle Characteristics:	See Appendix
Models/Type References:	See Appendix
Brand Name:	JA SOLAR
Relevant Standards:	EN 61000-6-3:2007+A1:2011 EN 61000-6-2:2005 The EMC directive 2014/30/EU
Verification Issuing Office Name & Address:	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Test Report Number(s):	230501326SHA-001



**Signature**

**Name: Edwin Xu**

**Position: Assistant Manager**

**Date: June 1, 2023**

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## APPENDIX: Test Verification of Conformity

This is an Appendix to Test Verification of Conformity Number: 230501326SHA-V1.

Models/Type References:

Maximum System Voltage: 1500 V DC or 1000 V DC	
Model	Rated Output Power at STC
JAM78S30-580/MR, JAM78S30-585/MR, JAM78S30-590/MR, JAM78S30-595/MR, JAM78S30-600/MR, JAM78S30-605/MR	580 W, 585 W, 590 W, 595 W, 600 W, 605 W
JAM72S30-535/MR, JAM72S30-540/MR, JAM72S30-545/MR, JAM72S30-550/MR, JAM72S30-555/MR	535 W, 540 W, 545 W, 550 W, 555 W
JAM66S30-480/MR, JAM66S30-485/MR, JAM66S30-490/MR, JAM66S30-495/MR, JAM66S30-500/MR, JAM66S30-505/MR	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S30-435/MR, JAM60S30-440/MR, JAM60S30-445/MR, JAM60S30-450/MR, JAM60S30-455/MR, JAM60S30-460/MR	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S30-390/MR, JAM54S30-395/MR, JAM54S30-400/MR, JAM54S30-405/MR, JAM54S30-410/MR, JAM54S30-415/MR, JAM54S30-420/MR, JAM54S30-425/MR	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM78S30-580/GR, JAM78S30-585/GR, JAM78S30-590/GR, JAM78S30-595/GR, JAM78S30-600/GR, JAM78S30-605/GR, JAM78S30-610/GR, JAM78S30-615/GR	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W, 615 W
JAM72S30-535/GR, JAM72S30-540/GR, JAM72S30-545/GR, JAM72S30-550/GR, JAM72S30-555/GR, JAM72S30-560/GR, JAM72S30-565/GR	535 W, 540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM66S30-480/GR, JAM66S30-485/GR, JAM66S30-490/GR, JAM66S30-495/GR, JAM66S30-500/GR, JAM66S30-505/GR, JAM66S30-510/GR, JAM66S30-515/GR	480 W, 485 W, 490 W, 495 W, 500 W, 505 W, 510 W, 515 W
JAM60S30-435/GR, JAM60S30-440/GR, JAM60S30-445/GR, JAM60S30-450/GR, JAM60S30-455/GR, JAM60S30-460/GR, JAM60S30-465/GR, JAM60S30-470/GR	435 W, 440 W, 445 W, 450 W, 455 W, 460 W, 465 W, 470 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM54S30-390/GR, JAM54S30-395/GR, JAM54S30-400/GR, JAM54S30-405/GR, JAM54S30-410/GR, JAM54S30-415/GR, JAM54S30-420/GR, JAM54S30-425/GR	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM72S40-545/GR, JAM72S40-550/GR, JAM72S40-555/GR, JAM72S40-560/GR, JAM72S40-565/GR, JAM72S40-570/GR, JAM72S40-575/GR	545 W, 550 W, 555 W, 560 W, 565 W, 570 W, 575 W
JAM66S40-500/GR, JAM66S40-505/GR, JAM66S40-510/GR, JAM66S40-515/GR, JAM66S40-520/GR, JAM66S40-525/GR	500 W, 505 W, 510 W, 515 W, 520 W, 525 W
JAM60S40-450/GR, JAM60S40-455/GR, JAM60S40-460/GR, JAM60S40-465/GR, JAM60S40-470/GR, JAM60S40-475/GR	450 W, 455 W, 460 W, 465 W, 470 W, 475 W
JAM54S40-405/GR, JAM54S40-410/GR, JAM54S40-415/GR, JAM54S40-420/GR, JAM54S40-425/GR, JAM54S40-430/GR, JAM54S40-435/GR	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W
JAM72S31-530/MR, JAM72S31-535/MR, JAM72S31-540/MR, JAM72S31-545/MR, JAM72S31-550/MR	530 W, 540 W, 540 W, 545 W, 550 W
JAM66S31-475/MR, JAM66S31-480/MR, JAM66S31-485/MR, JAM66S31-490/MR, JAM66S31-495/MR, JAM66S31-500/MR	475 W, 480 W, 485 W, 490 W, 495 W, 500 W
JAM60S31-430/MR, JAM60S31-435/MR, JAM60S31-440/MR, JAM60S31-445/MR, JAM60S31-450/MR, JAM60S31-455/MR	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54S31-390/MR, JAM54S31-395/MR, JAM54S31-400/MR, JAM54S31-405/MR, JAM54S31-410/MR, JAM54S31-415/MR	390 W, 395 W, 400 W, 405 W, 410 W, 415 W
JAM78S31-570/GR, JAM78S31-575/GR, JAM78S31-580/GR, JAM78S31-585/GR, JAM78S31-590/GR, JAM78S31-595/GR, JAM78S31-600/GR	570 W, 575 W, 580 W, 585 W, 590 W, 595 W, 600 W
JAM72S31-530/GR, JAM72S31-535/GR, JAM72S31-540/GR, JAM72S31-545/GR, JAM72S31-550/GR, JAM72S31-555/GR	530 W, 535 W, 540 W, 545 W, 550 W, 550 W, 555 W
JAM66S31-480/GR, JAM66S31-485/GR, JAM66S31-490/GR, JAM66S31-495/GR, JAM66S31-500/GR, JAM66S31-505/GR	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S31-435/GR, JAM60S31-440/GR, JAM60S31-445/GR, JAM60S31-450/GR, JAM60S31-455/GR, JAM60S31-460/GR	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S31-395/GR, JAM54S31-400/GR, JAM54S31-405/GR, JAM54S31-410/GR, JAM54S31-415/GR, JAM54S31-420/GR	395 W, 400 W, 405 W, 410 W, 415 W, 420 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM72S41-545/GR, JAM72S41-550/GR, JAM72S41-555/GR, JAM72S41-560/GR, JAM72S41-565/GR, JAM72S41-570/GR,	545 W, 550 W, 555 W, 560 W, 565 W, 570 W
JAM66S41-500/GR, JAM66S41-505/GR, JAM66S41-510/GR, JAM66S41-515/GR, JAM66S41-520/GR	500 W, 505 W, 510 W, 515 W, 520 W
JAM60S41-450/GR, JAM60S41-455/GR, JAM60S41-460/GR, JAM60S41-465/GR, JAM60S41-470/GR	450 W, 455 W, 460 W, 465 W, 470 W
JAM54S41-405/GR, JAM54S41-410/GR, JAM54S41-415/GR, JAM54S41-420/GR, JAM54S41-425/GR, JAM54S41-430/GR,	405 W, 410 W, 415 W, 420 W, 425 W, 430 W,
JAM66S35-645/MR, JAM66S35-650/MR, JAM66S35-655/MR, JAM66S35-660/MR, JAM66S35-665/MR, JAM66S35-670/MR	645 W, 650 W, 655 W, 660 W, 665 W, 670 W
JAM60S35-585/MR, JAM60S35-590/MR, JAM60S35-595/MR, JAM60S35-600/MR, JAM60S35-605/MR, JAM60S35-610/MR	585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM72S30-555/LR, JAM72S30-560/LR, JAM72S30-565/LR, JAM72S30-570/LR, JAM72S30-575/LR, JAM72S30-580/LR, JAM72S30-585/LR	555 W, 560 W, 565 W, 570 W, 575 W, 580 W, 585 W
JAM54S30-410/LR, JAM54S30-415/LR, JAM54S30-420/LR, JAM54S30-425/LR, JAM54S30-430/LR, JAM54S30-435/LR, JAM54S30-440/LR	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LR, JAM54S31-415/LR, JAM54S31-420/LR, JAM54S31-425/LR, JAM54S31-430/LR, JAM54S31-435/LR, JAM54S31-440/LR	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-410/LB, JAM54S30-415/LB, JAM54S30-420/LB, JAM54S30-425/LB, JAM54S30-430/LB, JAM54S30-435/LB, JAM54S30-440/LB	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LB, JAM54S31-415/LB, JAM54S31-420/LB, JAM54S31-425/LB, JAM54S31-430/LB, JAM54S31-435/LB, JAM54S31-440/LB	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-390/MB, JAM54S30-395/MB, JAM54S30-400/MB, JAM54S30-405/MB, JAM54S30-410/MB, JAM54S30-415/MB, JAM54S30-420/MB, JAM54S30-425/MB	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM54S31-390/MB, JAM54S31-395/MB, JAM54S31-400/MB, JAM54S31-405/MB, JAM54S31-410/MB, JAM54S31-415/MB	390 W, 395 W, 400 W, 405 W, 410 W, 415 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Maximum System Voltage: 1500 V DC	
Model	Rated Output Power at STC
JAM78S30-580/MR/1500V, JAM78S30-585/MR/1500V, JAM78S30-590/MR/1500V, JAM78S30-595/MR/1500V, JAM78S30-600/MR/1500V, JAM78S30-605/MR/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W
JAM72S30-535/MR/1500V, JAM72S30-540/MR/1500V, JAM72S30-545/MR/1500V, JAM72S30-550/MR/1500V, JAM72S30-555/MR/1500V	535 W, 540 W, 545 W, 550 W, 555 W
JAM66S30-480/MR/1500V, JAM66S30-485/MR/1500V, JAM66S30-490/MR/1500V, JAM66S30-495/MR/1500V, JAM66S30-500/MR/1500V, JAM66S30-505/MR/1500V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S30-435/MR/1500V, JAM60S30-440/MR/1500V, JAM60S30-445/MR/1500V, JAM60S30-450/MR/1500V, JAM60S30-455/MR/1500V, JAM60S30-460/MR/1500V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S30-390/MR/1500V, JAM54S30-395/MR/1500V, JAM54S30-400/MR/1500V, JAM54S30-405/MR/1500V, JAM54S30-410/MR/1500V, JAM54S30-415/MR/1500V, JAM54S30-420/MR/1500V, JAM54S30-425/MR/1500V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM78S30-580/GR/1500V, JAM78S30-585/GR/1500V, JAM78S30-590/GR/1500V, JAM78S30-595/GR/1500V, JAM78S30-600/GR/1500V, JAM78S30-605/GR/1500V, JAM78S30-610/GR/1500V, JAM78S30-615/GR/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W, 615 W
JAM72S30-535/GR/1500V, JAM72S30-540/GR/1500V, JAM72S30-545/GR/1500V, JAM72S30-550/GR/1500V, JAM72S30-555/GR/1500V, JAM72S30-560/GR/1500V, JAM72S30-565/GR/1500V	535 W, 540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM66S30-480/GR/1500V, JAM66S30-485/GR/1500V, JAM66S30-490/GR/1500V, JAM66S30-495/GR/1500V, JAM66S30-500/GR/1500V, JAM66S30-505/GR/1500V, JAM66S30-510/GR/1500V, JAM66S30-515/GR/1500V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W, 510 W, 515 W
JAM60S30-435/GR/1500V, JAM60S30-440/GR/1500V, JAM60S30-445/GR/1500V, JAM60S30-450/GR/1500V, JAM60S30-455/GR/1500V, JAM60S30-460/GR/1500V, JAM60S30-465/GR/1500V, JAM60S30-470/GR/1500V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W, 465 W, 470 W
JAM54S30-390/GR/1500V, JAM54S30-395/GR/1500V, JAM54S30-400/GR/1500V, JAM54S30-405/GR/1500V, JAM54S30-410/GR/1500V, JAM54S30-415/GR/1500V, JAM54S30-420/GR/1500V, JAM54S30-425/GR/1500V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM72S40-545/GR/1500V, JAM72S40-550/GR/1500V, JAM72S40-555/GR/1500V, JAM72S40-560/GR/1500V, JAM72S40-565/GR/1500V, JAM72S40-570/GR/1500V, JAM72S40-575/GR/1500V	545 W, 550 W, 555 W, 560 W, 565 W, 570 W, 575 W
JAM66S40-500/GR/1500V, JAM66S40-505/GR/1500V, JAM66S40-510/GR/1500V, JAM66S40-515/GR/1500V, JAM66S40-520/GR/1500V, JAM66S40-525/GR/1500V	500 W, 505 W, 510 W, 515 W, 520 W, 525 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM60S40-450/GR/1500V, JAM60S40-455/GR/1500V, JAM60S40-460/GR/1500V, JAM60S40-465/GR/1500V, JAM60S40-470/GR/1500V, JAM60S40-475/GR/1500V	450 W, 455 W, 460 W, 465 W, 470 W, 475 W
JAM54S40-405/GR/1500V, JAM54S40-410/GR/1500V, JAM54S40-415/GR/1500V, JAM54S40-420/GR/1500V, JAM54S40-425/GR/1500V, JAM54S40-430/GR/1500V, JAM54S40-435/GR/1500V	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W
JAM72S31-530/MR/1500V, JAM72S31-535/MR/1500V, JAM72S31-540/MR/1500V, JAM72S31-545/MR/1500V, JAM72S31-550/MR/1500V	530 W, 540 W, 540 W, 545 W, 550 W
JAM66S31-475/MR/1500V, JAM66S31-480/MR/1500V, JAM66S31-485/MR/1500V, JAM66S31-490/MR/1500V, JAM66S31-495/MR/1500V, JAM66S31-500/MR/1500V	475 W, 480 W, 485 W, 490 W, 495 W, 500 W
JAM60S31-430/MR/1500V, JAM60S31-435/MR/1500V, JAM60S31-440/MR/1500V, JAM60S31-445/MR/1500V, JAM60S31-450/MR/1500V, JAM60S31-455/MR/1500V	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54S31-390/MR/1500V, JAM54S31-395/MR/1500V, JAM54S31-400/MR/1500V, JAM54S31-405/MR/1500V, JAM54S31-410/MR/1500V, JAM54S31-415/MR/1500V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W
JAM78S31-570/GR/1500V, JAM78S31-575/GR/1500V, JAM78S31-580/GR/1500V, JAM78S31-585/GR/1500V, JAM78S31-590/GR/1500V, JAM78S31-595/GR/1500V, JAM78S31-600/GR/1500V	570 W, 575 W, 580 W, 585 W, 590 W, 595 W, 600 W
JAM72S31-530/GR/1500V, JAM72S31-535/GR/1500V, JAM72S31-540/GR/1500V, JAM72S31-545/GR/1500V, JAM72S31-550/GR/1500V, JAM72S31-555/GR/1500V	530 W, 535 W, 540 W, 545 W, 550 W, 555 W
JAM66S31-480/GR/1500V, JAM66S31-485/GR/1500V, JAM66S31-490/GR/1500V, JAM66S31-495/GR/1500V, JAM66S31-500/GR/1500V, JAM66S31-505/GR/1500V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S31-435/GR/1500V, JAM60S31-440/GR/1500V, JAM60S31-445/GR/1500V, JAM60S31-450/GR/1500V, JAM60S31-455/GR/1500V, JAM60S31-460/GR/1500V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S31-395/GR/1500V, JAM54S31-400/GR/1500V, JAM54S31-405/GR/1500V, JAM54S31-410/GR/1500V, JAM54S31-415/GR/1500V, JAM54S31-420/GR/1500V	395 W, 400 W, 405 W, 410 W, 415 W, 420 W
JAM72S41-545/GR/1500V, JAM72S41-550/GR/1500V, JAM72S41-555/GR/1500V, JAM72S41-560/GR/1500V, JAM72S41-565/GR/1500V, JAM72S41-570/GR/1500V,	545 W, 550 W, 555 W, 560 W, 565 W, 570 W,
JAM66S41-500/GR/1500V, JAM66S41-505/GR/1500V, JAM66S41-510/GR/1500V, JAM66S41-515/GR/1500V, JAM66S41-520/GR/1500V	500 W, 505 W, 510 W, 515 W, 520 W
JAM60S41-450/GR/1500V, JAM60S41-455/GR/1500V, JAM60S41-460/GR/1500V, JAM60S41-465/GR/1500V, JAM60S41-470/GR/1500V	450 W, 455 W, 460 W, 465 W, 470 W
JAM54S41-405/GR/1500V, JAM54S41-410/GR/1500V, JAM54S41-415/GR/1500V, JAM54S41-420/GR/1500V, JAM54S41-425/GR/1500V, JAM54S41-430/GR/1500V,	405 W, 410 W, 415 W, 420 W, 425 W, 430 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM66S35-645/MR/1500V, JAM66S35-650/MR/1500V, JAM66S35-655/MR/1500V, JAM66S35-660/MR/1500V, JAM66S35-665/MR/1500V, JAM66S35-670/MR/1500V	645 W, 650 W, 655 W, 660 W, 665 W, 670 W
JAM60S35-585/MR/1500V, JAM60S35-590/MR/1500V, JAM60S35-595/MR/1500V, JAM60S35-600/MR/1500V, JAM60S35-605/MR/1500V, JAM60S35-610/MR/1500V	585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM72S30-555/LR/1500V, JAM72S30-560/LR/1500V, JAM72S30-565/LR/1500V, JAM72S30-570/LR/1500V, JAM72S30-575/LR/1500V, JAM72S30-580/LR/1500V, JAM72S30-585/LR/1500V	555 W, 560 W, 565 W, 570 W, 575 W, 580 W, 585 W
JAM54S30-410/LR/1500V, JAM54S30-415/LR/1500V, JAM54S30-420/LR/1500V, JAM54S30-425/LR/1500V, JAM54S30-430/LR/1500V, JAM54S30-435/LR/1500V, JAM54S30-440/LR/1500V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LR/1500V, JAM54S31-415/LR/1500V, JAM54S31-420/LR/1500V, JAM54S31-425/LR/1500V, JAM54S31-430/LR/1500V, JAM54S31-435/LR/1500V, JAM54S31-440/LR/1500V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-410/LB/1500V, JAM54S30-415/LB/1500V, JAM54S30-420/LB/1500V, JAM54S30-425/LB/1500V, JAM54S30-430/LB/1500V, JAM54S30-435/LB/1500V, JAM54S30-440/LB/1500V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LB/1500V, JAM54S31-415/LB/1500V, JAM54S31-420/LB/1500V, JAM54S31-425/LB/1500V, JAM54S31-430/LB/1500V, JAM54S31-435/LB/1500V, JAM54S31-440/LB/1500V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-390/MB/1500V, JAM54S30-395/MB/1500V, JAM54S30-400/MB/1500V, JAM54S30-405/MB/1500V, JAM54S30-410/MB/1500V, JAM54S30-415/MB/1500V, JAM54S30-420/MB/1500V, JAM54S30-425/MB/1500V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM54S31-390/MB/1500V, JAM54S31-395/MB/1500V, JAM54S31-400/MB/1500V, JAM54S31-405/MB/1500V, JAM54S31-410/MB/1500V, JAM54S31-415/MB/1500V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W

Maximum System Voltage: 1000 V DC	
Model	Rated Output Power at STC
JAM78S30-580/MR/1000V, JAM78S30-585/MR/1000V, JAM78S30-590/MR/1000V, JAM78S30-595/MR/1000V, JAM78S30-600/MR/1000V, JAM78S30-605/MR/1000V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W
JAM72S30-535/MR/1000V, JAM72S30-540/MR/1000V, JAM72S30-545/MR/1000V, JAM72S30-550/MR/1000V, JAM72S30-555/MR/1000V	535 W, 540 W, 545 W, 550 W, 555 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM66S30-480/MR/1000V, JAM66S30-485/MR/1000V, JAM66S30-490/MR/1000V, JAM66S30-495/MR/1000V, JAM66S30-500/MR/1000V, JAM66S30-505/MR/1000V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S30-435/MR/1000V, JAM60S30-440/MR/1000V, JAM60S30-445/MR/1000V, JAM60S30-450/MR/1000V, JAM60S30-455/MR/1000V, JAM60S30-460/MR/1000V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S30-390/MR/1000V, JAM54S30-395/MR/1000V, JAM54S30-400/MR/1000V, JAM54S30-405/MR/1000V, JAM54S30-410/MR/1000V, JAM54S30-415/MR/1000V, JAM54S30-420/MR/1000V, JAM54S30-425/MR/1000V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM78S30-580/GR/1000V, JAM78S30-585/GR/1000V, JAM78S30-590/GR/1000V, JAM78S30-595/GR/1000V, JAM78S30-600/GR/1000V, JAM78S30-605/GR/1000V, JAM78S30-610/GR/1000V, JAM78S30-615/GR/1000V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W, 615 W
JAM72S30-535/GR/1000V, JAM72S30-540/GR/1000V, JAM72S30-545/GR/1000V, JAM72S30-550/GR/1000V, JAM72S30-555/GR/1000V, JAM72S30-560/GR/1000V, JAM72S30-565/GR/1000V	535 W, 540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM66S30-480/GR/1000V, JAM66S30-485/GR/1000V, JAM66S30-490/GR/1000V, JAM66S30-495/GR/1000V, JAM66S30-500/GR/1000V, JAM66S30-505/GR/1000V, JAM66S30-510/GR/1000V, JAM66S30-515/GR/1000V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W, 510 W, 515 W
JAM60S30-435/GR/1000V, JAM60S30-440/GR/1000V, JAM60S30-445/GR/1000V, JAM60S30-450/GR/1000V, JAM60S30-455/GR/1000V, JAM60S30-460/GR/1000V, JAM60S30-465/GR/1000V, JAM60S30-470/GR/1000V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W, 465 W, 470 W
JAM54S30-390/GR/1000V, JAM54S30-395/GR/1000V, JAM54S30-400/GR/1000V, JAM54S30-405/GR/1000V, JAM54S30-410/GR/1000V, JAM54S30-415/GR/1000V, JAM54S30-420/GR/1000V, JAM54S30-425/GR/1000V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM72S40-545/GR/1000V, JAM72S40-550/GR/1000V, JAM72S40-555/GR/1000V, JAM72S40-560/GR/1000V, JAM72S40-565/GR/1000V, JAM72S40-570/GR/1000V, JAM72S40-575/GR/1000V	545 W, 550 W, 555 W, 560 W, 565 W, 570 W, 575 W
JAM66S40-500/GR/1000V, JAM66S40-505/GR/1000V, JAM66S40-510/GR/1000V, JAM66S40-515/GR/1000V, JAM66S40-520/GR/1000V, JAM66S40-525/GR/1000V	500 W, 505 W, 510 W, 515 W, 520 W, 525 W
JAM60S40-450/GR/1000V, JAM60S40-455/GR/1000V, JAM60S40-460/GR/1000V, JAM60S40-465/GR/1000V, JAM60S40-470/GR/1000V, JAM60S40-475/GR/1000V	450 W, 455 W, 460 W, 465 W, 470 W, 475 W
JAM54S40-405/GR/1000V, JAM54S40-410/GR/1000V, JAM54S40-415/GR/1000V, JAM54S40-420/GR/1000V, JAM54S40-425/GR/1000V, JAM54S40-430/GR/1000V, JAM54S40-435/GR/1000V	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W
JAM72S31-530/MR/1000V, JAM72S31-535/MR/1000V, JAM72S31-540/MR/1000V, JAM72S31-545/MR/1000V, JAM72S31-550/MR/1000V	530 W, 540 W, 540 W, 545 W, 550 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



JAM66S31-475/MR/1000V, JAM66S31-480/MR/1000V, JAM66S31-485/MR/1000V, JAM66S31-490/MR/1000V, JAM66S31-495/MR/1000V, JAM66S31-500/MR/1000V	475 W, 480 W, 485 W, 490 W, 495 W, 500 W
JAM60S31-430/MR/1000V, JAM60S31-435/MR/1000V, JAM60S31-440/MR/1000V, JAM60S31-445/MR/1000V, JAM60S31-450/MR/1000V, JAM60S31-455/MR/1000V	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54S31-390/MR/1000V, JAM54S31-395/MR/1000V, JAM54S31-400/MR/1000V, JAM54S31-405/MR/1000V, JAM54S31-410/MR/1000V, JAM54S31-415/MR/1000V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W
JAM78S31-570/GR/1000V, JAM78S31-575/GR/1000V, JAM78S31-580/GR/1000V, JAM78S31-585/GR/1000V, JAM78S31-590/GR/1000V, JAM78S31-595/GR/1000V, JAM78S31-600/GR/1000V	570 W, 575 W, 580 W, 585 W, 590 W, 595 W, 600 W
JAM72S31-530/GR/1000V, JAM72S31-535/GR/1000V, JAM72S31-540/GR/1000V, JAM72S31-545/GR/1000V, JAM72S31-550/GR/1000V, JAM72S31-555/GR/1000V	530 W, 535 W, 540 W, 545 W, 550 W, 555 W
JAM66S31-480/GR/1000V, JAM66S31-485/GR/1000V, JAM66S31-490/GR/1000V, JAM66S31-495/GR/1000V, JAM66S31-500/GR/1000V, JAM66S31-505/GR/1000V	480 W, 485 W, 490 W, 495 W, 500 W, 505 W
JAM60S31-435/GR/1000V, JAM60S31-440/GR/1000V, JAM60S31-445/GR/1000V, JAM60S31-450/GR/1000V, JAM60S31-455/GR/1000V, JAM60S31-460/GR/1000V	435 W, 440 W, 445 W, 450 W, 455 W, 460 W
JAM54S31-395/GR/1000V, JAM54S31-400/GR/1000V, JAM54S31-405/GR/1000V, JAM54S31-410/GR/1000V, JAM54S31-415/GR/1000V, JAM54S31-420/GR/1000V	395 W, 400 W, 405 W, 410 W, 415 W, 420 W
JAM72S41-545/GR/1000V, JAM72S41-550/GR/1000V, JAM72S41-555/GR/1000V, JAM72S41-560/GR/1000V, JAM72S41-565/GR/1000V, JAM72S41-570/GR/1000V	545 W, 550 W, 555 W, 560 W, 565 W, 570 W
JAM66S41-500/GR/1000V, JAM66S41-505/GR/1000V, JAM66S41-510/GR/1000V, JAM66S41-515/GR/1000V, JAM66S41-520/GR/1000V	500 W, 505 W, 510 W, 515 W, 520 W
JAM60S41-450/GR/1000V, JAM60S41-455/GR/1000V, JAM60S41-460/GR/1000V, JAM60S41-465/GR/1000V, JAM60S41-470/GR/1000V	450 W, 455 W, 460 W, 465 W, 470 W
JAM54S41-405/GR/1000V, JAM54S41-410/GR/1000V, JAM54S41-415/GR/1000V, JAM54S41-420/GR/1000V, JAM54S41-425/GR/1000V, JAM54S41-430/GR/1000V	405 W, 410 W, 415 W, 420 W, 425 W, 430 W
JAM66S35-645/MR/1000V, JAM66S35-650/MR/1000V, JAM66S35-655/MR/1000V, JAM66S35-660/MR/1000V, JAM66S35-665/MR/1000V, JAM66S35-670/MR/1000V	645 W, 650 W, 655 W, 660 W, 665 W, 670 W
JAM66S35-585/MR/1000V, JAM66S35-590/MR/1000V, JAM66S35-595/MR/1000V, JAM66S35-600/MR/1000V, JAM66S35-605/MR/1000V, JAM66S35-610/MR/1000V	585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM72S30-555/LR/1000V, JAM72S30-560/LR/1000V, JAM72S30-565/LR/1000V, JAM72S30-570/LR/1000V, JAM72S30-575/LR/1000V, JAM72S30-580/LR/1000V	555 W, 560 W, 565 W, 570 W, 575 W, 580 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM72S30-585/LR/1000V	585 W
JAM54S30-410/LR/1000V, JAM54S30-415/LR/1000V, JAM54S30-420/LR/1000V, JAM54S30-425/LR/1000V, JAM54S30-430/LR/1000V, JAM54S30-435/LR/1000V, JAM54S30-440/LR/1000V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LR/1000V, JAM54S31-415/LR/1000V, JAM54S31-420/LR/1000V, JAM54S31-425/LR/1000V, JAM54S31-430/LR/1000V, JAM54S31-435/LR/1000V, JAM54S31-440/LR/1000V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-410/LB/1000V, JAM54S30-415/LB/1000V, JAM54S30-420/LB/1000V, JAM54S30-425/LB/1000V, JAM54S30-430/LB/1000V, JAM54S30-435/LB/1000V, JAM54S30-440/LB/1000V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S31-410/LB/1000V, JAM54S31-415/LB/1000V, JAM54S31-420/LB/1000V, JAM54S31-425/LB/1000V, JAM54S31-430/LB/1000V, JAM54S31-435/LB/1000V, JAM54S31-440/LB/1000V	410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54S30-390/MB/1000V, JAM54S30-395/MB/1000V, JAM54S30-400/MB/1000V, JAM54S30-405/MB/1000V, JAM54S30-410/MB/1000V, JAM54S30-415/MB/1000V, JAM54S30-420/MB/1000V, JAM54S30-425/MB/1000V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W, 420 W, 425 W
JAM54S31-390/MB/1000V, JAM54S31-395/MB/1000V, JAM54S31-400/MB/1000V, JAM54S31-405/MB/1000V, JAM54S31-410/MB/1000V, JAM54S31-415/MB/1000V	390 W, 395 W, 400 W, 405 W, 410 W, 415 W

Maximum System Voltage: 1500 V DC	
Model	Rated Output Power at STC
JAM78D30-585/MB, JAM78D30-590/MB, JAM78D30-595/MB, JAM78D30-600/MB, JAM78D30-605/MB, JAM78D30-610/MB	585 W, 590 W, 595 W, 600 W, 605 W, 610W
JAM72D30-535/MB, JAM72D30-540/MB, JAM72D30-545/MB, JAM72D30-550/MB, JAM72D30-555/MB	535 W, 540 W, 545 W, 550 W, 555 W
JAM66D30-485/MB, JAM66D30-490/MB, JAM66D30-495/MB, JAM66D30-500/MB, JAM66D30-505/MB	485 W, 490 W, 495 W, 500 W, 505 W
JAM60D30-440/MB, JAM60D30-445/MB, JAM60D30-450/MB, JAM60D30-455/MB, JAM60D30-460/MB	440 W, 445 W, 450 W, 455 W, 460 W
JAM54D30-395/MB, JAM54D30-400/MB, JAM54D30-405/MB, JAM54D30-410/MB, JAM54D30-415/MB	395 W, 400 W, 405 W, 410 W, 415 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM54D31-395/MB, JAM54D31-400/MB, JAM54D31-405/MB, JAM54D31-410/MB, JAM54D31-415/MB	395 W, 400 W, 405 W, 410 W, 415 W
JAM78D30-585/MB/1500V, JAM78D30-590/MB/1500V, JAM78D30-595/MB/1500V, JAM78D30-600/MB/1500V, JAM78D30-605/MB/1500V, JAM78D30-610/MB/1500V	585 W, 590 W, 595 W, 600 W, 605 W, 610W
JAM72D30-535/MB/1500V, JAM72D30-540/MB/1500V, JAM72D30-545/MB/1500V, JAM72D30-550/MB/1500V, JAM72D30-555/MB/1500V	535 W, 540 W, 545 W, 550 W, 555 W
JAM66D30-485/MB/1500V, JAM66D30-490/MB/1500V, JAM66D30-495/MB/1500V, JAM66D30-500/MB/1500V, JAM66D30-505/MB/1500V	485 W, 490 W, 495 W, 500 W, 505 W
JAM60D30-440/MB/1500V, JAM60D30-445/MB/1500V, JAM60D30-450/MB/1500V, JAM60D30-455/MB/1500V, JAM60D30-460/MB/1500V	440 W, 445 W, 450 W, 455 W, 460 W
JAM54D30-395/MB/1500V, JAM54D30-400/MB/1500V, JAM54D30-405/MB/1500V, JAM54D30-410/MB/1500V, JAM54D30-415/MB/1500V	395 W, 400 W, 405 W, 410 W, 415 W
JAM54D31-395/MB/1500V, JAM54D31-400/MB/1500V, JAM54D31-405/MB/1500V, JAM54D31-410/MB/1500V, JAM54D31-415/MB/1500V	395 W, 400 W, 405 W, 410 W, 415 W
JAM66D35-645/MB, JAM66D35-650/MB, JAM66D35-655/MB, JAM66D35-660/MB, JAM66D35-665/MB, JAM66D35-670/MB	645 W, 650 W, 655 W, 660 W, 665 W, 670 W
JAM60D35-585/MB, JAM60D35-590/MB, JAM60D35-595/MB, JAM60D35-600/MB, JAM60D35-605/MB, JAM60D35-610/MB	585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM66D35-645/MB/1500V, JAM66D35-650/MB/1500V, JAM66D35-655/MB/1500V, JAM66D35-660/MB/1500V, JAM66D35-665/MB/1500V, JAM66D35-670/MB/1500V	645 W, 650 W, 655 W, 660 W, 665 W, 670 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM60D35-585/MB/1500V, JAM60D35-590/MB/1500V, JAM60D35-595/MB/1500V, JAM60D35-600/MB/1500V, JAM60D35-605/MB/1500V, JAM60D35-610/MB/1500V	585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM78D40-580/GB, JAM78D40-585/GB, JAM78D40-590/GB, JAM78D40-595/GB, JAM78D40-600/GB, JAM78D40-605/GB, JAM78D40-610/GB, JAM78D40-615/GB, JAM78D40-620/GB, JAM78D40-625/GB, JAM78D40-630/GB, JAM78D40-635/GB	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W, 615 W, 620 W, 625 W, 630 W, 635 W
JAM72D40-540/GB, JAM72D40-545/GB, JAM72D40-550/GB, JAM72D40-555/GB, JAM72D40-560/GB, JAM72D40-565/GB, JAM72D40-570/GB, JAM72D40-575/GB, JAM72D40-580/GB, JAM72D40-585/GB	540 W, 545 W, 550 W, 555 W, 560 W, 565 W, 570 W, 575 W, 580 W, 585 W
JAM66D40-500/GB, JAM66D40-505/GB, JAM66D40-510/GB, JAM66D40-515/GB, JAM66D40-520/GB, JAM66D40-525/GB, JAM66D40-530/GB, JAM66D40-535/GB	500 W, 505 W, 510 W, 515 W, 520 W, 525 W, 530 W, 535 W
JAM60D40-455/GB, JAM60D40-460/GB, JAM60D40-465/GB, JAM60D40-470/GB, JAM60D40-475/GB, JAM60D40-480/GB, JAM60D40-485/GB	455 W, 460 W, 465 W, 470 W, 475 W, 480 W, 485 W
JAM54D40-405/GB, JAM54D40-410/GB, JAM54D40-415/GB, JAM54D40-420/GB, JAM54D40-425/GB, JAM54D40-430/GB, JAM54D40-435/GB, JAM54D40-440/GB	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54D41-405/GB, JAM54D41-410/GB, JAM54D41-415/GB, JAM54D41-420/GB, JAM54D41-425/GB, JAM54D41-430/GB, JAM54D41-435/GB	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W
JAM78D40-580/GB/1500V, JAM78D40-585/GB/1500V, JAM78D40-590/GB/1500V, JAM78D40-595/GB/1500V, JAM78D40-600/GB/1500V, JAM78D40-605/GB/1500V, JAM78D40-610/GB/1500V, JAM78D40-615/GB/1500V, JAM78D40-620/GB/1500V, JAM78D40-625/GB/1500V, JAM78D40-630/GB/1500V, JAM78D40-635/GB/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W, 615 W, 620 W, 625 W, 630 W, 635 W
JAM72D40-540/GB/1500V, JAM72D40-545/GB/1500V, JAM72D40-550/GB/1500V,	540 W, 545 W, 550 W, 555 W, 560 W, 565 W,

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM72D40-555/GB/1500V, JAM72D40-560/GB/1500V, JAM72D40-565/GB/1500V, JAM72D40-570/GB/1500V, JAM72D40-575/GB/1500V, JAM72D40-580/GB/1500V, JAM72D40-585/GB/1500V	570 W, 575 W, 580 W, 585 W
JAM66D40-500/GB/1500V, JAM66D40-505/GB/1500V, JAM66D40-510/GB/1500V, JAM66D40-515/GB/1500V, JAM66D40-520/GB/1500V, JAM66D40-525/GB/1500V, JAM66D40-530/GB/1500V, JAM66D40-535/GB/1500V	500 W, 505 W, 510 W, 515 W, 520 W, 525 W, 530 W, 535 W
JAM60D40-455/GB/1500V, JAM60D40-460/GB/1500V, JAM60D40-465/GB/1500V, JAM60D40-470/GB/1500V, JAM60D40-475/GB/1500V, JAM60D40-480/GB/1500V, JAM60D40-485/GB/1500V	455 W, 460 W, 465 W, 470 W, 475 W, 480 W, 485 W
JAM54D40-405/GB/1500V, JAM54D40-410/GB/1500V, JAM54D40-415/GB/1500V, JAM54D40-420/GB/1500V, JAM54D40-425/GB/1500V, JAM54D40-430/GB/1500V, JAM54D40-435/GB/1500V, JAM54D40-440/GB/1500V	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W, 440 W
JAM54D41-405/GB/1500V, JAM54D41-410/GB/1500V, JAM54D41-415/GB/1500V, JAM54D41-420/GB/1500V, JAM54D41-425/GB/1500V, JAM54D41-430/GB/1500V, JAM54D41-435/GB/1500V	405 W, 410 W, 415 W, 420 W, 425 W, 430 W, 435 W
JAM78D30-580/GB, JAM78D30-585/GB, JAM78D30-590/GB, JAM78D30-595/GB, JAM78D30-600/GB, JAM78D30-605/GB, JAM78D30-615/GB	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 615 W
JAM72D30-540/GB, JAM72D30-545/GB, JAM72D30-550/GB, JAM72D30-555/GB, JAM72D30-560/GB, JAM72D30-565/GB	540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM66D30-495/GB, JAM66D30-500/GB, JAM66D30-505/GB, JAM66D30-510/GB, JAM66D30-515/GB, JAM66D30-520/GB	495 W, 500 W, 505 W, 510 W, 515 W, 520 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM60D30-450/GB, JAM60D30-455/GB, JAM60D30-460/GB, JAM60D30-465/GB, JAM60D30-470/GB	450 W, 455 W, 460 W, 465 W, 470 W
JAM54D30-405/GB, JAM54D30-410/GB, JAM54D30-415/GB, JAM54D30-420/GB, JAM54D30-425/GB	405 W, 410 W, 415 W, 420 W, 425 W
JAM54D31-405/GB, JAM54D31-410/GB, JAM54D31-415/GB, JAM54D31-420/GB, JAM54D31-425/GB	405 W, 410 W, 415 W, 420 W, 425 W
JAM78D30-580/GB/1500V, JAM78D30-585/GB/1500V, JAM78D30-590/GB/1500V, JAM78D30-595/GB/1500V, JAM78D30-600/GB/1500V, JAM78D30-605/GB/1500V, JAM78D30-615/GB/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 615 W
JAM72D30-540/GB/1500V, JAM72D30-545/GB/1500V, JAM72D30-550/GB/1500V, JAM72D30-555/GB/1500V, JAM72D30-560/GB/1500V, JAM72D30-565/GB/1500V	540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM66D30-495/GB/1500V, JAM66D30-500/GB/1500V, JAM66D30-505/GB/1500V, JAM66D30-510/GB/1500V, JAM66D30-515/GB/1500V, JAM66D30-520/GB/1500V	495 W, 500 W, 505 W, 510 W, 515 W, 520 W
JAM60D30-450/GB/1500V, JAM60D30-455/GB/1500V, JAM60D30-460/GB/1500V, JAM60D30-465/GB/1500V, JAM60D30-470/GB/1500V	450 W, 455 W, 460 W, 465 W, 470 W
JAM54D30-405/GB/1500V, JAM54D30-410/GB/1500V, JAM54D30-415/GB/1500V, JAM54D30-420/GB/1500V, JAM54D30-425/GB/1500V	405 W, 410 W, 415 W, 420 W, 425 W
JAM54D31-405/GB/1500V, JAM54D31-410/GB/1500V, JAM54D31-415/GB/1500V, JAM54D31-420/GB/1500V, JAM54D31-425/GB/1500V	405 W, 410 W, 415 W, 420 W, 425 W
JAM78D40-610/MB, JAM78D40-615/MB, JAM78D40-620/MB, JAM78D40-625/MB, JAM78D40-630/MB	610 W, 615 W, 620 W, 625 W, 630 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM72D40-560/MB, JAM72D40-565/MB, JAM72D40-570/MB, JAM72D40-575/MB, JAM72D40-580/MB, JAM72D40-585/MB	560 W, 565 W, 570 W, 575 W, 580 W, 585 W
JAM66D40-500/MB, JAM66D40-505/MB, JAM66D40-510/MB, JAM66D40-515/MB, JAM66D40-520/MB, JAM66D40-525/MB, JAM66D40-530/MB	500 W, 505 W, 510 W, 515 W, 520 W, 525 W, 530 W
JAM60D40-455/MB, JAM60D40-460/MB, JAM60D40-465/MB, JAM60D40-470/MB, JAM60D40-475/MB, JAM60D40-480/MB	455 W, 460 W, 465 W, 470 W, 475 W, 480 W
JAM54D40-415/MB, JAM54D40-420/MB, JAM54D40-425/MB, JAM54D40-430/MB, JAM54D40-435/MB	415 W, 420 W, 425 W, 430 W, 435 W
JAM72D40-580/HB, JAM72D40-585/HB, JAM72D40-590/HB, JAM72D40-595/HB, JAM72D40-600/HB, JAM72D40-605/HB, JAM72D40-610/HB	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM54D40-430/HB, JAM54D40-435/HB, JAM54D40-440/HB, JAM54D40-445/HB, JAM54D40-450/HB, JAM54D40-455/HB	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54D41-425/HB, JAM54D41-430/HB, JAM54D41-435/HB, JAM54D41-440/HB, JAM54D41-445/HB, JAM54D41-450/HB, JAM54D41-455/HB	425 W, 430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM66D45-595/LB, JAM66D45-600/LB, JAM66D45-605/LB, JAM66D45-610/LB, JAM66D45-615/LB, JAM66D45-620/LB, JAM66D45-625/LB	595 W, 600 W, 605 W, 610 W, 615 W, 620 W, 625 W
JAM60D45-540/LB, JAM60D45-545/LB, JAM60D45-550/LB, JAM60D45-555/LB, JAM60D45-560/LB, JAM60D45-565/LB	540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM72D40-580/LB, JAM72D40-585/LB, JAM72D40-590/LB, JAM72D40-595/LB, JAM72D40-600/LB, JAM72D40-605/LB	580 W, 585 W, 590 W, 595 W, 600 W, 605 W
JAM54D40-430/LB, JAM54D40-435/LB, JAM54D40-440/LB, JAM54D40-445/LB, JAM54D40-450/LB, JAM54D40-455/LB	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54D41-425/LB, JAM54D41-430/LB, JAM54D41-435/LB, JAM54D41-440/LB, JAM54D41-445/LB, JAM54D41-450/LB, JAM54D41-455/LB	425 W, 430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM72D42-605/LB, JAM72D42-610/LB, JAM72D42-615/LB, JAM72D42-620/LB, JAM72D42-625/LB, JAM72D42-630/LB	605 W, 610 W, 615 W, 620 W, 625 W, 630 W
JAM72D30-555/LB, JAM72D30-560/LB, JAM72D30-565/LB, JAM72D30-570/LB, JAM72D30-575/LB, JAM72D30-580/LB	555 W, 560 W, 565 W, 570 W, 575 W, 580 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM54D30-415/LB, JAM54D30-420/LB, JAM54D30-425/LB, JAM54D30-430/LB, JAM54D30-435/LB	415 W, 420 W, 425 W, 430 W, 435 W
JAM54D31-415/LB, JAM54D31-420/LB, JAM54D31-425/LB, JAM54D31-430/LB, JAM54D31-435/LB	415 W, 420 W, 425 W, 430 W, 435 W
JAM78D40-610/MB/1500V, JAM78D40-615/MB/1500V, JAM78D40-620/MB/1500V, JAM78D40-625/MB/1500V, JAM78D40-630/MB/1500V	610 W, 615 W, 620 W, 625 W, 630 W
JAM72D40-560/MB/1500V, JAM72D40-565/MB/1500V, JAM72D40-570/MB/1500V, JAM72D40-575/MB/1500V, JAM72D40-580/MB/1500V, JAM72D40-585/MB/1500V	560 W, 565 W, 570 W, 575 W, 580 W, 585 W
JAM66D40-500/MB/1500V, JAM66D40-505/MB/1500V, JAM66D40-510/MB/1500V, JAM66D40-515/MB/1500V, JAM66D40-520/MB/1500V, JAM66D40-525/MB/1500V, JAM66D40-530/MB/1500V	500 W, 505 W, 510 W, 515 W, 520 W, 525 W, 530 W
JAM60D40-455/MB/1500V, JAM60D40-460/MB/1500V, JAM60D40-465/MB/1500V, JAM60D40-470/MB/1500V, JAM60D40-475/MB/1500V, JAM60D40-480/MB/1500V	455 W, 460 W, 465 W, 470 W, 475 W, 480 W
JAM54D40-415/MB/1500V, JAM54D40-420/MB/1500V, JAM54D40-425/MB/1500V, JAM54D40-430/MB/1500V, JAM54D40-435/MB/1500V	415 W, 420 W, 425 W, 430 W, 435 W
JAM72D40-580/HB/1500V, JAM72D40-585/HB/1500V, JAM72D40-590/HB/1500V, JAM72D40-595/HB/1500V, JAM72D40-600/HB/1500V, JAM72D40-605/HB/1500V, JAM72D40-610/HB/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W, 610 W
JAM54D40-430/HB/1500V, JAM54D40-435/HB/1500V, JAM54D40-440/HB/1500V, JAM54D40-445/HB/1500V, JAM54D40-450/HB/1500V	430 W, 435 W, 440 W, 445 W, 450 W, 455 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



JAM54D40-455/HB/1500V	
JAM54D41-425/HB/1500V, JAM54D41-430/HB/1500V, JAM54D41-435/HB/1500V, JAM54D41-440/HB/1500V, JAM54D41-445/HB/1500V, JAM54D41-450/HB/1500V, JAM54D41-455/HB/1500V	425 W, 430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM66D45-595/LB/1500V, JAM66D45-600/LB/1500V, JAM66D45-605/LB/1500V, JAM66D45-610/LB/1500V, JAM66D45-615/LB/1500V, JAM66D45-620/LB/1500V, JAM66D45-625/LB/1500V	595 W, 600 W, 605 W, 610 W, 615 W, 620 W, 625 W
JAM60D45-540/LB/1500V, JAM60D45-545/LB/1500V, JAM60D45-550/LB/1500V, JAM60D45-555/LB/1500V, JAM60D45-560/LB/1500V, JAM60D45-565/LB/1500V	540 W, 545 W, 550 W, 555 W, 560 W, 565 W
JAM72D40-580/LB/1500V, JAM72D40-585/LB/1500V, JAM72D40-590/LB/1500V, JAM72D40-595/LB/1500V, JAM72D40-600/LB/1500V, JAM72D40-605/LB/1500V	580 W, 585 W, 590 W, 595 W, 600 W, 605 W
JAM54D40-430/LB/1500V, JAM54D40-435/LB/1500V, JAM54D40-440/LB/1500V, JAM54D40-445/LB/1500V, JAM54D40-450/LB/1500V, JAM54D40-455/LB/1500V	430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM54D41-425/LB/1500V, JAM54D41-430/LB/1500V, JAM54D41-435/LB/1500V, JAM54D41-440/LB/1500V, JAM54D41-445/LB/1500V, JAM54D41-450/LB/1500V, JAM54D41-455/LB/1500V	425 W, 430 W, 435 W, 440 W, 445 W, 450 W, 455 W
JAM72D42-605/LB/1500V, JAM72D42-610/LB/1500V, JAM72D42-615/LB/1500V, JAM72D42-620/LB/1500V, JAM72D42-625/LB/1500V, JAM72D42-630/LB/1500V	605 W, 610 W, 615 W, 620 W, 625 W, 630 W

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM72D30-555/LB/1500V, JAM72D30-560/LB/1500V, JAM72D30-565/LB/1500V, JAM72D30-570/LB/1500V, JAM72D30-575/LB/1500V, JAM72D30-580/LB/1500V	555 W, 560 W, 565 W, 570 W, 575 W, 580 W
JAM54D30-415/LB/1500V, JAM54D30-420/LB/1500V, JAM54D30-425/LB/1500V, JAM54D30-430/LB/1500V, JAM54D30-435/LB/1500V	415 W, 420 W, 425 W, 430 W, 435 W
JAM54D31-415/LB/1500V, JAM54D31-420/LB/1500V, JAM54D31-425/LB/1500V, JAM54D31-430/LB/1500V, JAM54D31-435/LB/1500V	415 W, 420 W, 425 W, 430 W, 435 W



**Signature**

**Name: Edwin Xu**

**Position: Assistant Manager**

**Date: June 1, 2023**

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.