

# LIMEA CONNECT

SLI028113NW\_PW



Power	<b>50 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>7700 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>08</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

---

Code	SLI028113NW_PW
Power	50 W
Nominal current	223 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	7700 lm (360°)
Luminous flux**	6000 lm (360°)
Lamp efficacy	154 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	PC/PC
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	1500x64x60 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 16 pcs per linei ,

## Related documents

---



 User manual



 Declaration of Conformity

---

