

XEDOS


Oprawa rastrowa natynkowa / Ceiling louver fitting




XEDOS 228 NT-EVG



XEDOS 414 NT-EVG




XEDOS 228 NT-EVG



XEDOS 414 NT-EVG

- ▶ obudowa: blacha stalowa / odbłyśnik: aluminium
- ▶ casing: steel sheet / reflector: aluminum

krzywa rozsyłu światłości /
curve of intensity distribution
 $\eta = 58\%$



Kanlux				
XEDOS 228 NT-EVG	08600	biały / white	2 x 28	2760
XEDOS 414 NT-EVG	04832	biały / white	4 x 14	3280

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

AKCESORIA / ACCESSORIES

ROPE-NT 150 SINGLE	07871	linka stalowa (pojedyncza) do zawieszenia oprawy XEDOS 414 NT-EVG, 2 szt. w komplecie / steel cord (single) for hanging XEDOS 414 NT-EVG, 2 pcs in set
ROPE-NT 150	07870	linka stalowa (podwójna) do zawieszenia oprawy XEDOS 228 NT-EVG, 2 szt. w komplecie / steel cord (double) for hanging XEDOS 228 NT-EVG, 2 pcs in set




- ▶ standardowy odbłyśnik w kształcie półparaboli
- ▶ standard semi-parabolic reflector



- ▶ przewód ochronny na rastrze, dodatkowo zabezpieczający przed porażeniem elektrycznym
- ▶ protective conductor on the raster, protecting additionally against electric shock



- ▶ poprzeczki rastra w kształcie „V”
- ▶ louver fitting cross-bars „V”-shaped



- ▶ gniazda świetlówek zamaskowane odbłyśnikiem
- ▶ reflector-masked fluorescent lamp sockets



- ▶ w komplecie rękawiczka foliowa
- ▶ plastic foil glove included in the set



- ▶ mała wysokość oprawy
- ▶ small height of fitting



- ▶ w obudowie otwory ułatwiające zasilanie przelotowe
- ▶ the holes in the housing to facilitate through-feeding