

Sterownik LED do taśm RGB

Controller to RGB led strips.



WIFI

30m



- Sterownik LED to pięciokanałowy (RGB+CCT) odbiornik RF.
- Technologia 2,4GHz, system działa do 30m.
- Odbiornik o stałym napięciu, z pięcioma wyjściami.
- Pełna kompatybilność z różnymi pilotami, RGB+CCT.
- Wiele stref można kontrolować oddzielnie lub synchronicznie z nieskończoną liczbą odbiorników w każdej strefie.
- Płynna zmiana kolorów jak i ich przyciemnianie od 0,1% do 100%.
- Jeden sterownik oświetlenia RF może współpracować z dziesięcioma pilotami.
- Jeden odbiornik może przesłać sygnał z pilota do innego odbiornika w odległości 15 m.
- Całkowita odległość zdalnego sterowania wynosi około 100 m.
- Odbiornik może być sterowany poprzez Wi-Fi – za pomocą aplikacji zainstalowanej na urządzeniach mobilnych z systemami IOS lub Android, podczas pracy ze sterownikiem WiFi-Relay.
- Odbiornik współpracuje ze wzmacniaczami.

- 5 channel RF 2.4G controller, default as RGB+CCT type, need match RGB+CCT remote, create colorful static or dynamic effect.
- Can also be used as dual color temperature or dimming controller, good compatibility.
- Full compatibility with a variety of RGB+CCT remote.
- Smooth dimming and switch without any flickering.
- When control RGB+CCT lamp, built in 10 dynamic mode, include jump or gradual change style.
- Adopt 2.4GHz wireless technology, remote distance up to 30m, can accept up to 10 remote control.
- Auto-transmitting function, one receiver can transmit the signal from the remote to another receiver within 15m, so the remote control distance can be beyond 100m.
- Auto-synchronization function, different receivers can work synchronously when they are controlled by the same remote, under same dynamic mode and same speed.
- Can be WiFi controlled by APP installed on IOS or Android mobile devices while working with WiFi-Relay controller.
- 5CH CV RF controller can connect unlimited number of 5CH CV or CC power repeaters in series or in parallel to expand output power.



PD027316



5908293927316



12V 5x(max 48W)



24V 5x(max 96W)



12-24V



5CH, 4A/1CH



do 30m



0,1% - 100%



20



170 x 50 x 23



100 000



-30/+55

Sterownik współpracuje m.in. z pilotami

Controller cooperates with pilots:



PD027255

5908293927255

PD027262

5908293927262

